



SUPPLEMENTAL/BID BULLETIN NO. 1

Date: October 16, 2024
Title: IB-2024-10-32 SUPPLY AND DELIVERY OF VARIOUS LABORATORY TOOLS AND EQUIPMENT
Reference No.: 11297201

This bulletin is being issued to revise/clarify certain portions of the bidding documents. This shall form an integral part of the bidding document for the above-mentioned procurement project.

GENERAL QUERIES	AMMENDMENTS/ CLARIFICATIONS
<ul style="list-style-type: none"> I suggest that the Committee require an authorized distributor certificate issued by the manufacturer for the items under Lot 2. 	<ul style="list-style-type: none"> Yes, the Authorized distributorship Certificate from the Manufacturer shall be required to be submitted and/or presented during the Post Qualification stage. Please see Annex "A" for the amended Bid Data Sheet.
<ul style="list-style-type: none"> Since there are pictures posted on PhilGEPS that display the brand, I suggest that the Committee require authorized trainers or personnel for the items in Lot 2. 	<ul style="list-style-type: none"> Yes, the Authorized Trainer Certificate from the Manufacturer shall be required to be submitted and/or presented during the Post Qualification stage. Please see Annex "A" for the amended Bid Data Sheet.
<ul style="list-style-type: none"> There is a typo error in the I want to be clarified with the switching diode, is this 5000 pcs per set? 	<ul style="list-style-type: none"> The required Switching Diode shall be 50PCS per set. Please see Annex "B" for the amended Technical Specifications.
<ul style="list-style-type: none"> I just want to be clarified about the online submission. Do we still need to submit manual copies if we opted for electronic bid submission. When will the date of submission be for electronic as well as for manual bids? 	<ul style="list-style-type: none"> For online submission, electronic bids must be submitted on or before October 24, 2024, at 1:30 PM (BAC Secretariat time). Hard copies of the bid are still required for the Post Qualification, which will begin on October 29, 2024, at 2:00 PM.

All statements and formats referring to this clause should be amended/corrected accordingly.

For guidance and information of all concerned.

For further information, please refer to:

(SGD) VINCENT B. CABANTOC
 Head, BAC Secretariat
 CP No. 0953-355-7046 - TM
 Email Add: evsu.bacsecretariat@evsu.edu.ph

Noted:

(SGD) BENEDICTO T. MILITANTE, JR., Ph.D., J.D.
 Vice President for Administration & Finance
 Chairperson, Bids and Awards Committee



Bid Data Sheet

ITB Clause									
5.3	<p>For this purpose, contracts similar to the Project shall be:</p> <p style="margin-left: 40px;">a. SUPPLY AND DELIVERY OF VARIOUS LABORATORY TOOLS AND EQUIPMENT</p> <p style="margin-left: 40px;">b. completed within two (2) years prior to the deadline for the submission and receipt of bids.</p>								
7.1	Subcontracting is not allowed.								
9	<p>Prospective bidders may submit their written request for clarification on and/or interpretation of any part of the Bidding Documents, either to EVSU BAC Secretariat Office or through electronic mail at evsu.bacsecretariat@evsu.edu.ph not later than October 14, 2024 (5:00 PM). Clarifications made and submitted beyond the abovementioned date shall not be accepted and/or entertained further.</p>								
14.1	<p>The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts:</p> <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="width: 70%;">FORMS OF BID SECURITY</th> <th style="width: 30%;">AMOUNT OF BID SECURITY (EQUAL TO PERCENTAGE OF THE ABC)</th> </tr> </thead> <tbody> <tr> <td>• Bid Securing Declaration; OR</td> <td style="text-align: center;">NOTARIZED</td> </tr> <tr> <td>• Cash, Cashier's/ manager's check issued by a Universal or Commercial Bank; OR</td> <td style="text-align: center;">Two Percent (2%)</td> </tr> <tr> <td>• Surety Bond (If security bond, attach the original copy of the official receipt of premium payment and certification issued by the Insurance Commission)</td> <td style="text-align: center;">Five Percent (5%)</td> </tr> </tbody> </table>	FORMS OF BID SECURITY	AMOUNT OF BID SECURITY (EQUAL TO PERCENTAGE OF THE ABC)	• Bid Securing Declaration; OR	NOTARIZED	• Cash, Cashier's/ manager's check issued by a Universal or Commercial Bank; OR	Two Percent (2%)	• Surety Bond (If security bond, attach the original copy of the official receipt of premium payment and certification issued by the Insurance Commission)	Five Percent (5%)
FORMS OF BID SECURITY	AMOUNT OF BID SECURITY (EQUAL TO PERCENTAGE OF THE ABC)								
• Bid Securing Declaration; OR	NOTARIZED								
• Cash, Cashier's/ manager's check issued by a Universal or Commercial Bank; OR	Two Percent (2%)								
• Surety Bond (If security bond, attach the original copy of the official receipt of premium payment and certification issued by the Insurance Commission)	Five Percent (5%)								
15.2	<p>Each Bidder shall submit one (1) original and four (4) readable authenticated copies of the first and second components of its bid. Documents to be submitted shall be properly tabbed and labeled according to the title of the document attached for prompt identification: e.g., PhilGEPS Certificate of Registration (Platinum) – PhilGEPS</p> <p>For details in the preparation of sealed bids, please refer to the diagram below:</p> <p style="margin-left: 40px;"><i>Figure 1. Sealing of Bids (Illustration of bids with 1 original and 4 copies, each box in the diagram represents a sealed envelope)</i></p> <div style="text-align: center; margin-top: 20px;"> </div>								

All envelopes shall:

- be addressed to the Procuring Entity’s BAC;
- bear the name and address of the Bidder in capital letters;
- contain the name of the contract to be bid in capital letters;
- bear the specific identification of this bidding process indicated in the ITB Clause 1; and bear a warning “DO NOT OPEN BEFORE...” the date and time for the opening of bids, as specified in the IB.

TO : **THE BIDS AND AWARDS COMMITTEE**
EASTERN VISAYAS STATE UNIVERSITY
 FROM : _____
(Name of Bidder in Capital Letters)
 ADDRESS : _____
(Address of Bidder in Capital Letters)
 BID REF. NO. : _____

(In Capital Letters, Indicate the Phrase):

“DO NOT OPEN BEFORE: _____”

15.3 Guidelines for Electronic Submission of Bids:





- The Bidder must submit a soft copy of their bids through e-mail to evsu.bacsecretariat@evsu.edu.ph at any time before **October 24, 2024, 1:30 P.M.**
- In the online submission of bids, a two-folder system will be utilized. The first folder contains the requirements of the Technical Component checklist as presented under Section VIII and shall be labeled “**TECHNICAL COMPONENT**”. The second folder contains the requirements of the Financial Component checklist and is marked “**FINANCIAL COMPONENT**”.
- The documentary requirements shall be segregated and labelled according to the type of document for prompt identification (e.g., PhilGEPS Certificate of Registration (Platinum) labelled as PhilGEPS) and each shall be in Portable Document Format (PDF).
- Each folder shall be compressed in Zip, RAR or 7z format with password protection. Submitted bidding documents that are not in compressed archive format and are not password protected, will be automatically rejected.
- The password for accessing the file shall be disclosed by the Bidders during the bid opening which may be done in person or face-to-face through videoconferencing, webcasting, e-mail or similar technology.
- An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.
- For further information, please refer to:
VINCENT B. CABANTOC
Head, BAC Secretariat
CP No. 0953-355-7046 - TM
Email Add: evsu.bacsecretariat@evsu.edu.ph




19.2 **Partial bid is allowed.** All Goods are grouped in items/lots listed below.

ITEM NO.	PARTICULARS	QTY	UNIT	TOTAL AMOUNT
1	PR NO. 05-0403-24 COE-ECE (ELECTRONIC LABORATORY EQUIPMENT)	1	Lot	92,024.00
2	PR NO. 09-0550-24 COE-ECE (ELECTRONIC LABORATORY EQUIPMENT)	1	Lot	880,000.00
3	PR NO. 09-0555-24 COE-CHE (CHEMICAL LABORATORY APPARATUS AND EQUIPMENT)	1	Lot	2,979,238.00
4	PR NO. 05-0428-24 CAS (HPLC ACCESSORIES AND SUPPLIES)	1	Lot	250,000.00
5	PR NO. 05-0422-24 CAS (CHEMISTRY LABORATORY TOOLS, GLASSWARES AND SUPPLIES)	1	Lot	602,335.00

<p>19.5</p>	<p>The Net Financial Contracting Capacity (NFCC), which must be at least equal to the ABC to be bid, is calculated as follows:</p> <p>NFCC = [(Current assets minus current liabilities) (15)] minus the value of all outstanding or uncompleted portions of the projects under ongoing contracts, including awarded contracts yet to be started, coinciding with the contract to be bid.</p>
<p>20.1</p>	<p><i>Within a non-extendible period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, the Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and the following additional documents:</i></p> <ol style="list-style-type: none"> <i>1. Authorized distributorship Certificate from the Manufacturer</i> <i>2. Authorized Trainer Certificate from the Manufacturer</i>


Technical Specifications

SUPPLY AND DELIVERY OF VARIOUS LABORATORY TOOLS AND EQUIPMENT			
ITEM NO.	DESCRIPTION	STATEMENT OF COMPLIANCE COMPLY/ NOT COMPLY	
PR NO. 05-0403-24 COE-ECE (ELECTRONIC LABORATORY EQUIPMENT)			
	DESCRIPTION	QTY	UNIT
	WIRE STRIPPER, 0.8MM MIN, 2.6MM MAX, 155 MM CABLE TYPE SOLID 	5	Pcs
	THROUGH HOLE CERAMIC CAPACITOR KIT CAPACITANCE RANGE 100 PF --> 4700PF 	2	Kits
1	LOGIC GATES ICs and Passive Components <ul style="list-style-type: none"> - Quad 2-Input OR Logic Gate, 14-Pin PDIP (Tube of 25) - Quad 2-Input NOR Logic Gate, 14-Pin PDIP (Tube of 25) - Quad 2-Input NAND Logic Gate, 14-Pin PDIP (Tube of 25) - Quad 2-Input AND Logic Gate, 14-Pin PDIP (Tube of 25) - Quad 2-Input XOR Logic Gate, 14-Pin PDIP (Tube of 25) - 74LS04N HEX INVERTER, 14-Pin PDIP (Tube of 25) - Switching Diode, 1A 600V, 2-Pin DO-41 1N4005-T (50PCS) LED Starter Kit LED Parts Kit 	10	Sets
	DIGITAL MULTIMETER <ul style="list-style-type: none"> - Handheld Digital Multimeter 10A ac Max, 10A dc Max, 600V ac Max 	5	Sets


PR NO. 09-0550-24 COE-ECE (ELECTRONIC LABORATORY EQUIPMENT)			
	DESCRIPTION	QTY	UNIT
2	<p>BENCH TYPE PROGRAMMABLE POWER SUPPLY</p> <ul style="list-style-type: none"> - Programmable DC power supply, 3 independently controlled and isolated outputs - Two 32 V/3.2 A, one 2.5 V/3.3 V/5V/3.2Ax1, total 220 W 5-digit voltage/4-digit current display, minimum resolution: 1 mV/1 mA (SPD3303X) Timing function provides programmed output steps 4.3-inch true color TFT-LCD 480x272 display - 3 types of output modes: Independent, series (60 V max), and parallel (6.4 A max) 	2	units
	<p>SPECTRUM ANALYZER</p> <ul style="list-style-type: none"> - frequency range: 150kHz ~ 3GHz - Auto set function noise floor: $\geq -100\text{dBm}$ - RBW range: 30kHz, 100 kHz, 300kHz, 1MHz - ACPR/ CHPW/ OCBW measurement 3 traces in different colors split window function - Limit line function remote control software - Presentation material for training courses - Support interface: USB device/host, RS-232C 	2	Units
	<p>FUNCTION/ARBITRARY WAVEFORM GENERATOR</p> <ul style="list-style-type: none"> - dual-channel, with bandwidth up to 60 MHz, and amplitude up to 20 Vpp-150 MSa/s sampling rate, 14-bit vertical resolution, and 16 kpts waveform length innovative easy pulse technology, capable of generating lower-jitter pulse waveforms, brings a wide range and extreme high precision in pulse width and rise/fall time adjustment - special circuit for square wave function, can generate square waves up to 60MHz with jitter less than 300ps+0.05 ppm of period- plenty of analog and digital modulation types: AM, DSB-AM, FM, PM, FSK, ASK, PSK and PWM- sweep and burst functions harmonics generator function- waveform combining function- high precision frequency counter- standard interfaces: USB host, USB device (USBTMC), LAN (VXI-11)-4.3" TFT-LCD display 	2	Units





PR NO. 09-0555-24 COE-CHE (CHEMICAL LABORATORY APPARATUS AND EQUIPMENT)






DESCRIPTION	QTY	UNIT
-------------	-----	------





<p>ELECTRIC BUNSEN WITH CONTROLLER FEATURES</p> <ul style="list-style-type: none"> - Conical shaped heating element directs radiant heat to the top cavity - Top cowl deflects heat away from your hand - Air circulation from the vented housing keeps the base cool enough to hold during operation - Burner consumes less of power - Recommended controller is the MC5 - 2 neon indicators: “Power On” white neon light & “Bunsen Heater On” amber neon light. - Regulator control knob can be turned clockwise to increase power. - A rod support clamp is provided at the rear of each heating controller to take a standard 12.5mm (1/2”) diameter rod. <div style="text-align: center;">  </div> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Electric Bunsen</th> <th>Specifications</th> </tr> </thead> <tbody> <tr> <td>Max Temp.</td> <td>800°C</td> </tr> <tr> <td>Material</td> <td>Stainless Steel</td> </tr> <tr> <td>Dimensions (d x h)</td> <td>120mm x 177mm</td> </tr> <tr> <td>Power Supply, Controller</td> <td>230V 50/60Hz, 480W</td> </tr> </tbody> </table> <p>Inclusions:</p> <ul style="list-style-type: none"> - 1 unit – MC5 Controller 	Electric Bunsen	Specifications	Max Temp.	800°C	Material	Stainless Steel	Dimensions (d x h)	120mm x 177mm	Power Supply, Controller	230V 50/60Hz, 480W	1	Unit
Electric Bunsen	Specifications											
Max Temp.	800°C											
Material	Stainless Steel											
Dimensions (d x h)	120mm x 177mm											
Power Supply, Controller	230V 50/60Hz, 480W											


3

<p>FILTER PRESS</p> <p>Technical Specifications:</p> <ul style="list-style-type: none"> - Framework of AISI 304 stainless steel with castors - Feeding tank of AISI 304 stainless steel, with 100 l capacity, equipped with stirring system driven by submersible pump - Tank of AISI 304 stainless steel, with 100 l capacity, to collect the filtered water - Screw feeding pump with speed variator - Variable area flowmeter for the filtered liquid - Filter press of AISI 304 stainless steel with transparent Plexiglas frames to display the process - IP55 switchboard, complying with EC conformity mark, including synoptic diagram and ELCB - Piping and valves of AISI 304 and AISI 316 stainless steel - Emergency pushbutton - Power supply: 230 Vac 50 Hz single-phase - 1,5 kVA (Other voltage and frequency on request) - Dimensions: 1500 x 670 x 1600 mm - Weight: 150 kg <p>*With portable Turbidimeter</p> <div style="text-align: center;">  </div>	1	Unit
--	---	------

PR NO. 05-0428-24 CAS (HPLC ACCESSORIES AND SUPPLIES)																																	
DESCRIPTION		QTY	UNIT																														
4	HPLC COLUMN ACCESSORIES <ul style="list-style-type: none"> - Inertsil ODS-3 (C18) 4.6mm x 5cm x 250mm - (C18) 4.6, x 5mm x 150 mm - Guard Column - Nonsterile Nylon Syringe Filters, Pore: 0,45 (um), Housing Diameter 13 (mm), 100/pk - UPS (3kVa) 	1	Lot																														
	PREVENTIVE MAINTENANCE (PM) KIT FOR HPLC <ul style="list-style-type: none"> - Plunger seal (2pcs) - Assy, Line Filter (1pc) - Element sus Filter (5pcs) - Needle Seal Assy (1pc) 																																
	HPLC GRADE SOLVENTS <ul style="list-style-type: none"> - Acetonitrile (2bottles) (2.5L each) - Methanol (3bottles) (2.5L each) - Trifluoroacetic Acid (1 bottle) (2.5L each) 																																
PR NO. 05-0422-24 CAS (CHEMISTRY LABORATORY TOOLS, GLASSWARES AND SUPPLIES)																																	
DESCRIPTION		QTY	UNIT																														
5	MICROBIOLOGICAL INCUBATOR <table border="1"> <thead> <tr> <th colspan="2">TECHNICAL SPECIFICATIONS</th> </tr> </thead> <tbody> <tr> <td>Inner Dimension WXD_XH</td> <td>600 X 500 X 1200 mm</td> </tr> <tr> <td>Volume</td> <td>360 liters</td> </tr> <tr> <td>Circulating System</td> <td>Vertical flow</td> </tr> <tr> <td>Program Operation</td> <td>1 memory, Max 8 steps</td> </tr> <tr> <td>Door</td> <td>Single door, left side opening</td> </tr> <tr> <td>Sensor Port</td> <td>Ø23mm X 1 Front left side</td> </tr> <tr> <td>Safety Devices</td> <td>Overheat Prevention Device, Independent Overheat Prevention Device, Sensor/Heater Disconnection Alarm, Thermal Relay for Fan Motor, Leakage Breaker</td> </tr> <tr> <td>Shelves (Maximum Load)</td> <td>4 pieces (15kg per piece)</td> </tr> <tr> <td>Outer Dimension WXD_XH</td> <td>710 X 680 X 1730 mm</td> </tr> <tr> <td>Weight</td> <td>118 kg</td> </tr> <tr> <td>Temperature Range</td> <td>Room Temp +5°C - 100°C</td> </tr> <tr> <td>Temperature Distribution Accuracy</td> <td>± 1.5°C (at 37°C & 70°C)</td> </tr> <tr> <td>Power Demand</td> <td>AC 220/230/240V, 50/60 Hz</td> </tr> <tr> <td>Current</td> <td>5A</td> </tr> </tbody> </table> 	TECHNICAL SPECIFICATIONS		Inner Dimension WXD _X H	600 X 500 X 1200 mm	Volume	360 liters	Circulating System	Vertical flow	Program Operation	1 memory, Max 8 steps	Door	Single door, left side opening	Sensor Port	Ø23mm X 1 Front left side	Safety Devices	Overheat Prevention Device, Independent Overheat Prevention Device, Sensor/Heater Disconnection Alarm, Thermal Relay for Fan Motor, Leakage Breaker	Shelves (Maximum Load)	4 pieces (15kg per piece)	Outer Dimension WXD _X H	710 X 680 X 1730 mm	Weight	118 kg	Temperature Range	Room Temp +5°C - 100°C	Temperature Distribution Accuracy	± 1.5°C (at 37°C & 70°C)	Power Demand	AC 220/230/240V, 50/60 Hz	Current	5A	1	Unit
	TECHNICAL SPECIFICATIONS																																
	Inner Dimension WXD _X H	600 X 500 X 1200 mm																															
	Volume	360 liters																															
	Circulating System	Vertical flow																															
	Program Operation	1 memory, Max 8 steps																															
	Door	Single door, left side opening																															
	Sensor Port	Ø23mm X 1 Front left side																															
	Safety Devices	Overheat Prevention Device, Independent Overheat Prevention Device, Sensor/Heater Disconnection Alarm, Thermal Relay for Fan Motor, Leakage Breaker																															
	Shelves (Maximum Load)	4 pieces (15kg per piece)																															
	Outer Dimension WXD _X H	710 X 680 X 1730 mm																															
	Weight	118 kg																															
	Temperature Range	Room Temp +5°C - 100°C																															
	Temperature Distribution Accuracy	± 1.5°C (at 37°C & 70°C)																															
Power Demand	AC 220/230/240V, 50/60 Hz																																
Current	5A																																

<p>TEST TUBE, 10ML</p> <ul style="list-style-type: none"> - Material: High-quality borosilicate glass - Design: Flat bottom, with without graduation mark. - Compatibility: Suitable for use with common laboratory equipment such as centrifuges and spectrophotometers. 		<p>50</p>	<p>Pcs</p>
<p>SCREW-CAP TEST TUBE, 10ML</p> <ul style="list-style-type: none"> - Material: High-quality borosilicate glass - Design: Round bottom, without graduation marks and featuring precise screw caps to ensure a tight seal and prevent sample leakage. - Compatibility: Suitable for use with common laboratory equipment such as centrifuges and spectrophotometers. 		<p>50</p>	<p>pcs</p>
<p>MICROCENTRIFUGE TUBE, 1.5ML</p> <ul style="list-style-type: none"> - Material: Polypropylene construction for chemical resistance and durability. - Closure: Secure screw cap or snap cap to prevent sample leakage during centrifugation. - Compatibility: Compatible with microcentrifuges and thermal cyclers for PCR applications. - Graduation Marks: Clear and accurate volume markings for precise sample measurement. - Sterility: DNase or RNase free 		<p>1</p>	<p>Box</p>
<p>PCR TUBES, 0.2 ML</p> <ul style="list-style-type: none"> - Material: High-quality polypropylene for thermal stability and compatibility with PCR cycling. - Closure: Tight-fitting, flat caps to prevent sample evaporation and contamination. - Optics: Clear tubes for optical detection of PCR products, suitable for real-time PCR. - Compatibility: Designed to fit standard PCR thermal cyclers and heat blocks. - Sterility: DNase or RNase free 		<p>1</p>	<p>Box</p>
<p>MICROCENTRIFUGE RACK</p> <ul style="list-style-type: none"> - Material: Durable plastic for stability and longevity. Molded in handles provide a secure grip for transport. Matte side panel accepts tape or direct labeling - Capacity: Configured to accommodate multiple microcentrifuge tubes in standard 80-hole format - Design: Modular or stackable design for space-saving storage and convenient use. - Compatibility: Compatible with standard microcentrifuge tubes and PCR tubes. - Size: 22.7 x 6.7 x 2.7cm (8-15/16 x 2-5/8 x 1-1/16") - Laboratory conditions: Can be used for freezer storage down to -80°C (-112°F) and autoclavable at 121°C (250°F) 		<p>2</p>	<p>Box</p>

<p>PCR TUBE RACK</p> <ul style="list-style-type: none"> - Capacity: Configured to accommodate multiple PCR tubes in standard 96-well format - Material: Heat-resistant plastic or polypropylene construction for compatibility with thermal cyclers. - Lid: Transparent or opaque lid for protection against contamination and sample loss. - Grid Configuration: Clearly marked grid layout for easy sample identification and handling. - Laboratory conditions: Can be used for freezer storage down to -80°C (-112°F) and autoclavable at 121°C (250°F) - Sterility: RNase or DNase-free. 		<p>2</p>	<p>Box</p>	
<p>ERLENMEYER FLASK, 1000 ML</p> <ul style="list-style-type: none"> - Material: High-quality borosilicate glass for chemical resistance and thermal stability. - Neck Design: Narrow neck with a standard or wide-mouth opening for easy pouring and sampling. - Graduation Marks: Clearly marked volume graduations for accurate measurement of liquid volumes. - Compatibility: Suitable for use with various laboratory equipment such as shakers and stirrers. - Sterilization: Autoclavable for convenient sterilization and reuse in microbiological applications. 		<p>20</p>	<p>Pcs</p>	
<p>ERLENMEYER FLASK, 500 ML</p> <ul style="list-style-type: none"> - Material: High-quality borosilicate glass for chemical resistance and thermal stability. - Neck Design: Narrow neck with a standard or wide-mouth opening for easy pouring and sampling. - Graduation Marks: Clearly marked volume graduations for accurate measurement of liquid volumes. - Compatibility: Suitable for use with various laboratory equipment such as shakers and stirrers. - Sterilization: Autoclavable for convenient sterilization and reuse in microbiological applications. 		<p>20</p>	<p>Pcs</p>	
<p>ERLENMEYER FLASK, 250 ML</p> <ul style="list-style-type: none"> - Material: High-quality borosilicate glass for chemical resistance and thermal stability. - Neck Design: Narrow neck with a standard or wide-mouth opening for easy pouring and sampling. - Graduation Marks: Clearly marked volume graduations for accurate measurement of liquid volumes. - Compatibility: Suitable for use with various laboratory equipment such as shakers and stirrers. - Sterilization: Autoclavable for convenient sterilization and reuse in microbiological applications. 		<p>20</p>	<p>pcs</p>	

	<p>ERLENMEYER FLASK, 100 ML</p> <ul style="list-style-type: none"> - Material: High-quality borosilicate glass for chemical resistance and thermal stability. - Neck Design: Narrow neck with a standard or wide-mouth opening for easy pouring and sampling. - Graduation Marks: Clearly marked volume graduations for accurate measurement of liquid volumes. - Compatibility: Suitable for use with various laboratory equipment such as shakers and stirrers. - Sterilization: Autoclavable for convenient sterilization and reuse in microbiological applications. 		<p>20</p>	<p>Pcs</p>
--	---	--	-----------	------------

 (Name of Bidder/Company)

 (Signature Over Printed Name of Authorized Representative)

 (Designation)

 (Date)